

## **Feature-Based Cellular Texturing for Architectural Models**

Justin Legakis   Julie Dorsey   Steven Gortler

Massachusetts Institute  
of Technology

Harvard  
University

### **Introduction / Motivation**

- What is a **cellular texture** ?
- Separate **overall shape** of model from fine **repetitive detail**
- Patterns are affected by **features** of the underlying model
- Generate **3D cells** to texture a **3D object**

### **Related Work**

- **2D brick and stone patterns**  
Yessios 79, Miyata 90
- **Biologically-motivated cellular texturing**  
Fleischer *et al.* 95
- **Solid Texturing**  
Perlin 85, Worley 96
- **Floral ornamental patterns**  
Wong *et al.* 98

### **Related Work**

- **2D brick and stone patterns**  
Yessios 79, Miyata 90
- **Biologically-motivated cellular texturing**  
Fleischer *et al.* 95
- **Solid Texturing**  
Perlin 85, Worley 96
- **Floral ornamental patterns**  
Wong *et al.* 98

### **Related Work**

- **2D brick and stone patterns**  
Yessios 79, Miyata 90
- **Biologically-motivated cellular texturing**  
Fleischer *et al.* 95
- **Solid Texturing**  
Perlin 85, Worley 96
- **Floral ornamental patterns**  
Wong *et al.* 98

### **Related Work**

- **2D brick and stone patterns**  
Yessios 79, Miyata 90
- **Biologically-motivated cellular texturing**  
Fleischer *et al.* 95
- **Solid Texturing**  
Perlin 85, Worley 96
- **Floral ornamental patterns**  
Wong *et al.* 98

### *Contributions: What This Paper is About*

A **strategy** for generating 3D cellular textures on a 3D model:

- An **order** of cellular texturing operations
- Pattern coordination with **occupancy maps**
- The specification of patterns with a tree of **pattern generators**

### *Contributions: What This Paper is About*

A **strategy** for generating 3D cellular textures on a 3D model:

- An **order** of cellular texturing operations
- Pattern coordination with **occupancy maps**
- The specification of patterns with a tree of **pattern generators**

### *Geometry: Features*

- Cells are applied to **features** of the model: **corners**, **edges**, and **faces**
- Model serves as a **scaffolding** for cells
- Features can be labeled to capture **semantic information** about the model

### *Geometry: Features*

- Cells are applied to **features** of the model: **corners**, **edges**, and **faces**
- Model serves as a **scaffolding** for cells
- Features can be labeled to capture **semantic information** about the model


### *Geometry: Features*

- Cells are applied to **features** of the model: **corners**, **edges**, and **faces**
- Model serves as a **scaffolding** for cells
- Features can be labeled to capture **semantic information** about the model

### *Geometry: Features*

- Cells are applied to **features** of the model: **corners**, **edges**, and **faces**
- Model serves as a **scaffolding** for cells
- Features can be labeled to capture **semantic information** about the model

### Low Level Mesh (Geometry)



vertices , triangle edges , & triangles

### Ordering of Cellular Texturing Operations

- Cells on **edges** are **more constrained** than cells on **faces**
- Cells on **corners** are **more constrained** than cells on **edges**

Texturing order: 1) **Corners**  
2) **Edges**  
3) **Faces**

### Ordering of Cellular Texturing Operations

- Cells on **edges** are **more constrained** than cells on **faces**
- Cells on **corners** are **more constrained** than cells on **edges**

Texturing order: 1) **Corners** ←  
2) **Edges**  
3) **Faces**

### Ordering of Cellular Texturing Operations

- Cells on **edges** are **more constrained** than cells on **faces**
- Cells on **corners** are **more constrained** than cells on **edges**

Texturing order: 1) **Corners** ←  
2) **Edges**  
3) **Faces**

### Ordering of Cellular Texturing Operations

- Cells on **edges** are **more constrained** than cells on **faces**
- Cells on **corners** are **more constrained** than cells on **edges**

Texturing order: 1) **Corners**  
2) **Edges**  
3) **Faces** ←

### Occupancy Maps

- Binary map: **occupied** or **unoccupied**
- Keeps track of which regions of a feature have not yet been textured
- Initialized with cells from **adjacent** features
- Also useful for **clipping**


## Occupancy Maps

- Binary map: **occupied** or **unoccupied**
- Keeps track of which regions of a feature have not yet been textured
- Initialized with cells from **adjacent** features
- Also useful for **clipping**


## Pattern Generators

- Units of **code** that implement patterns
- Task segmented into **three functions**: cells for corners, edges, and faces
- Can **create cells** and/or **pass features** to other pattern generators
- Can make decisions based on **labels** or **geometric analysis**


### Example Pattern Generator Tree




### Example Pattern Generator Tree















### Example Pattern Generator Tree




### Example Pattern Generator Tree









### Geometric Analysis: Vertex Types




### Geometric Analysis: Vertex Types





### Geometric Analysis: Vertex Types




### Example Pattern Generator Tree



### Example Pattern Generator Tree





## Summary

**Algorithmically** generate 3D cellular textures that are the result of both a **pattern** and the full 3D geometry of the **underlying model**

### Strategy:

- Ordering: corners, edges, faces
- Occupancy maps
- Tree of pattern generators

## Future Work

- Experiment with more patterns
- Higher-level specification of patterns
- Mortar
- Different feature sets
- Higher-level constraint solving

SIGGRAPH

## Future Work

- Experiment with more patterns
- Higher-level specification of patterns
- Mortar
- Different feature sets
- Higher-level constraint solving

SIGGRAPH

## Acknowledgements

Special thanks to **Barb Cutler**, **Stephen Duck**, **John Alex**, **Frédéric Durand**, and the rest of the MIT Computer Graphics Group

### This work was supported by:

- NSF awards CCR-9624172 and CCR-9988535
- NSF CISE Research Infrastructure award EIA - 9802220
- Pixar Animation Studios